

## MEDICAL GRADE AIO PCs & MONITORS PLUS ACCESSORIES

Windows 11

S ACCESSORIES

EDITION 3.1

FREEWAYMEDTECH.COM

# CONTENTS

# 04

Why buy Freeway Med-Tech?

Check out the high quality components we use as standard equipment!

Plus, on page 6 a look at the competition's AIO PC tech.

# 06

MT500-24T MT500-22T

Battery-powered touch screen AIO Monitor/PC in 2 sizes.



# 16

Battery status LEDs explained

Information on our monitors' front-facing LED battery status indicators.

## 32

### MT400-24T MT400-27T

Mains-powered touch screen AIO Monitor/PC in 2 sizes.





All products available on NHS Supply Chain via eDirect.









#### 52 62 72 70 74 MT700-24T MT600-24T MT202 Lithium-ion MT202 6-bay Product cleaning battery pack battery charger and chemical guide Battery-powered 24in touch Mains-powered 24in touch Our off-unit charging accessory General cleaning information Technical information on our screen Monitor. screen Monitor. high quality, high capacity hotfor the MT202 Li-ion battery and use of suitable industrystandard chemical products. swappable batteries. packs.



# WHY BUY FREEWAY MED-TECH?

## Well, just look at the high specification components we use



#### More cores in our CPUs

We use 10th gen Intel CPUs which have as many as 4 times the number of cores compared with similar AIOs from other manufacturers.

#### Blazingly fast storage

We use mPCIe NVMe type SSD storage modules which are approx 5 times faster than competitors' commonly used SATA SSDs.

#### WiFi 6 networking

Not only faster than WiFi 5, but our WiFi 6 card ensures better compatibility with newer networks.

#### **COM** serial ports

Expansive connectivity with multiple COM ports as standard on our MT400 and MT500 products.

"2x serial ports MT500 / 3x serial ports MT400

## in our Medical Grade AIO PCs as <u>STANDARD</u> equipment.





#### Impressive Electrostatic Discharge Isolation

Up to 30kV isolation on USB, HDMI and Ethernet. This far exceeds most competitors' systems and the 60601 requirements!

#### On-screen display menus

Edit parameters like brightness, volume and wifi selection via a single function button and touch screen taps. Great for a clinical environment.

## Built-in mic and powerful stereo speaker system

An integral mic make our screens easily adapted for telemedicine applications with the optional camera added.

"Downward facing speakers result in a louder, brighter sound.

## Tech that is unrivalled at our price point!

Most of the features listed here are either optional extras or not available on other manufacturer's units.





# **MEDICAL AIO**

### **BATTERY POWERED / 24IN**



## Freeway Med-Tech's battery powered AIOs use desktop-class processors.


## Not all i5 CPUs are equal!


## Check out the comparisons opposite...

### Graph Performance Key >

Taller bars and higher numbers in the graphs indicate better performance. For example, a score of 10000 shows a CPU is twice as powerful as one rated at 5000.


Comparisons shown opposite, use the popular **Passmark Rating** generated via the website **www.cpubenchmark.net** 








Our competitors' CPU Passmark Rating\* VS the Freeway Med-Tech AIO processor family





NHS Trust's save £1000's by purchasing our i5 AIO for an entire fleet of workstations, when compared with purchasing a competitors' i7 model. AND, not only is there a huge cost saving, the performance would be better too! What's not to like?


## See yet more performance comparisons opposite...

Comparisons shown, use the popular **User Benchmark** scores generated via the website **cpu.userbenchmark.com** 



#### **MEDICAL AIO'S** - CPU COMPARISONS (USERBENCHMARK TESTS)







|   | Joseph W  | _            |           |  | A                                   |     | Arture 💬        |             |             |
|---|---|--------------|-----------|--|-------------------------------------|-----|-----------------|-------------|-------------|
| 2 | Thermore Profession   |              |           |  |                                     |     | Basely of       |             | -           |
| • | Lauran  | Dark.        | -         |  | 8/96/1903 /6.04<br>(0.06.0003 /6.04 |     | Francisc Martin | 7           |             |
|   |   |              |           |  |                                     | -   | 1000            | (           | 24/7        |
|   | Book Harry Party  | ARRAY        | strenest. | Climited   | DALE ROAD                           |     |                 |             |             |
|   | COLUMNICON  |              | metral    |  | 2010/00/001                         | 1   | _               |             |             |
|   | New Yorghand (1985)   |              |           |  | acris 610 (100                      |     | _               | NC          |             |
|   | Box Brook (107) Dark (1973)   | · add an one |           |  |                                     | 4   |                 | HOT-S       | WAPPA       |
| 0 | man for many party of the   |              | with m    |  |                                     |     |                 | P           | OWER        |
|   | The second second   |              | -         | And the state of the state   | P.76207.500                         | 1.  |                 |             |             |
|   | Assembland  |              |           | and in such as the   | 10.10.001.001                       | *   | -               | Contract of | 10000       |
|   | while these links (new particip   | · LT periet  | 10-00     |  | monant (im)                         | 1   | 目的時             |             |             |
|   |   |              | +10       |  | The second second                   |     | - 816           | 1 日日        | <b>#</b> 10 |
|   | Automation in the second se |              |           |  | Descenario                          | 100 |                 |             |             |
|   | Land Point Land Point Land Point Land   | see.cl       | RINNET.   |  | 100x101104                          | <., | 田田              | 458         | 4-5         |
|   | hausenin  |              | read      |  |                                     | 1   |                 |             |             |
|   | and the second second   | -            | ++21      | And the second s |                                     |     |                 |             |             |
|   | NEX Contrained  |              |           |  |                                     |     | 11113           | 1005-5      | 0.032       |

#### STATE-OF-THE-ART TOUCH SCREEN



10-point multi touch capacitive type screens as standard!

#### CHARGER DOCK (available separately)



Charge up to 6 Li-ion battery packs simultaneously!

#### PRODUCT CODE


## $\rm MT500\mathchar`24T$ Battery powered 24 in AlO touch screen medical grade monitor/PC

The Freeway Med-Tech MT500-24T Battery Powered All-In-One Monitor/PC offers fully mobile computing with its powerful, hot-swappable rechargeable battery packs. Options for 1, 2 or 3 Lithium-ion batteries allow for either an emergency power back up, or totally wire-free operation. Also features a handy built-in reading light.

#### DIMENSIONS

Height = 370.9mm Width = 564.4mm Depth = 41.2mm

#### PRODUCT ELEVATIONS




#### KEY FEATURES

- Uses up to 3 Lithium-ion batteries for a full shift of mobile operation
- No need to be near mains power
- Intel Core-i5/7/9 processors
- Runs Microsoft® Windows® / Linux / Igel
- DC outputs can power PC peripherals and other medical equipment
- High contrast 24" capacitive-type touch screen
- Slim fanless design
- UL60601 certified with anti-microbial enclosure
- Withstands common medical environment cleaning chemicals<sup>\*</sup>



REAR

100x100 VESA mounting



Uses up to 3 Li-ion batteries



FREEWAY ● U Med-Tech ● U



Water resistant enclosures

The screen and rear enclosure are IP rated against dust and moisture ingress, ensuring easy cleaning and disinfection\*.

\*See pages 194/5 for detailed information on cleaning chemicals and procedures.

| <br>1.0 | ľ |
|---------|---|
| ιe      | l |
|         |   |

Choice of processor

Modern Intel<sup>®</sup> Core-i5/7/9 range of processors to choose from.



**Optional DC-out** Can power PC peripherals and other medical equipment.



Battery status made easy

Front facing LED battery indicators offer feedback on the health of each battery.



Easily hot-swap battery packs in a matter of seconds




Clear battery status LEDs



The **OPTIONAL** DC-out can power PC peripherals!



Moisture resistant medical-grade front panel



A choice of 6 to 10 cores of Intel processing power.



#### Windows OS

IoT Enterprise version available for pre-install with or without license.

Linux/lgel operating systems can also be installed.

Industry standard OS for medical software and systems.



#### **TECHNICAL SPECIFICATIONS**

| System                  |   |       |
|-------------------------|---|-------|
| CPU                     | Intel <sup>®</sup> Core™ i5-10500T, 2.3 GHz (up to 3.8GHz) - <b>6 core</b><br>Intel <sup>®</sup> Core™ i7-10700T, 2.0 GHz (up to 4.5GHz) - <b>8 core</b><br>Intel <sup>®</sup> Core™ i9-10900T, 1.9 GHz (up to 4.6GHz) - <b>10 core</b> | intel |
| RAM                     | 8GB to 64GB   |       |
| Storage                 | 256Gb to 4TB Flash (mPCle NVMe type SSD)  |       |
| Operating System        | Microsoft® Windows®/Linux/Igel - specify pre-install if required  |       |
| Display                 | 23.8in capacitive touch screen  |       |
| Display resolution      | 1920×1080   |       |
| Trusted platform module | TPM 2.0   |       |
| Reading light           | LED reading light x I   |       |
| Microphone and speaker  | Built-in microphones and speaker  |       |
| Network Interface       |   |       |
| WLAN                    | Ethernet 10/100/1000 MB Base-T LAN; Wi-Fi 802.11ax, 2.4GHz/5GHz dual band   |       |
| Bluetooth               | Bluetooth 5.1   |       |
| I/O Ports               |   |       |
| USB Ports               | USB 2.0 x 2 and USB 3.0 x 4   |       |
| COM Port                | 2   |       |
| HDMI-out (1.4a)         | 1   |       |
|                         |   |       |
| Audio Jack              | 1   |       |
| Audio Jack<br>Ethernet  | I<br>RJ45 connector for ethernet × I  |       |
|                         | <br>RJ45 connector for ethernet ×  <br>   |       |

| Fanless  |
|--|
| Input: 100 – 240V AC; Output: 19V DC, 6.31A  |
| MT202 Li-ion battery; 85Wh, 7800mAh x 3 (optional)   |
| ABS + PC plastics, anti-microbial enclosure  |
| 370.9 x 564.4 x 41.2mm   |
| 7.4kg (without battery) - 8.8kg (with 3 batteries)   |
| 100mm × 100mm VESA standard  |
| Front panel: IP65; Enclosure: IPX2   |
| ANSI/AAMI ES60601-1, IEC60601-1, IEC60601-1-2, FCC Part 18, FCC Part 15 Class B, GB<br>17625.1, GB 4943.1, GB/T 9254, CE-EMC, CE-RED, RCM, CCC |
|  |
| Full-HD front camera   |
| Dual frequency, reads both 125KHz and 13.56MHz credentials   |
| Full-slot, reads ISO 7816T=0,T=1; 1.8/3/5V smart card  |
|  |



Optional Imprivata certified RFID reader



#### Faster processors than our competitors!

Our Intel® Core i5 CPU is effectively 30% faster in real-world benchmark tests.

| *Shorter bars are better  |          |                        |                   |
|---------------------------|----------|------------------------|-------------------|
| Our Competitors' i5 CPU   |          | Competitors'<br>CPU    | Med-Tech CPU      |
| Freeway Med-Tech's i5 CPU | <b>v</b> | STITE ANAL 522" / 1384 | PRINTER 200" (188 |

#### MT500-24T ACCESSORIES (available separately)



#### BATTERY STATUS EXPLAINED - MT700-24T / MT500-24T


#### Battery status. Constantly visible.

The Freeway Med-Tech MT500-24T (AIO) and the MT700-24T (Monitor) products feature an intuitive LED battery health indicator system that is always visible at the top of the panel.

Simply by glancing at the top left of the screen, the user can quickly see if the batteries are; fully charged, partly charged or are in need of immediate charging. The same indicators will also tell the user when the unit is plugged in and charging.

See the images opposite for the indication of each stage.





## So, what do the battery status LEDs mean?

## 

#### A blinking blue indicator...

This means the corresponding battery is charging.




#### A solid blue indicator...

This means the corresponding battery is charged 25% and above. No need to worry about charging in the near term.

#### BATTERY STATUS EXPLAINED - MT700-24T / MT500-24T







#### The on-screen menu



#### A solid orange indicator...

This means the corresponding battery is charged between 24-10%. The user should be aware that the pack will need charging soon.



711

#### A blinking orange indicator...

This means the corresponding battery is charged 9% or less. The user should swap out the battery or plug the iWOW into a mains socket (if applicable).



**Exact percentages** can be seen by entering the menu using the monitor's function buttons.

#### MT500-24T - PENTIUM™ PROCESSOR - STORAGE AND MEMORY CHOICE

#### Choose your performance spec based around the Intel<sup>®</sup> Pentium<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.


A standard warranty of 12 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT500-24T with Intel<sup>®</sup> Pentium<sup>™</sup> CPU

23.6in Medical Cart Computer with capacitive touch LCD, Intel<sup>®</sup> 10th Gen Pentium™ processor, medical grade AC/DC adapter.





\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.

#### MT500-24T - i5 PROCESSOR - STORAGE AND MEMORY CHOICE



#### Choose your performance spec based around the powerful Intel<sup>®</sup> i5 Core<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.

A standard warranty of I2 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT500-24T with Intel<sup>®</sup> i5 Core<sup>™</sup> CPU

23.6in Medical Cart Computer with capacitive touch LCD, Intel<sup>®</sup> 10th Gen i5 Core™ processor, medical grade AC/DC adapter:



| Window                         | 2511 24in             |         |           |                      |                       |
|--------------------------------|-----------------------|---------|-----------|----------------------|-----------------------|
| (B)<br>Base                    | -                     | HDD     | [0000000] | WARRANTY             | WARRANTY              |
| Part Number                    | Operating System      | Storage | RAM       | Standard<br>Warranty | Extended<br>Warranty* |
| MT500-24T-584T50-X- <b>495</b> | Specify when ordering | 256GB   | 8GB       | 12 months            | 60 months             |
| MT500-24T-584T50-X- <b>595</b> | Specify when ordering | 256GB   | I6GB      | 12 months            | 60 months             |

\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.

512GB

16GB

Specify when ordering

MT500-24T-584T50-X-5A5

60 months

12 months

#### MT500-24T - i7 PROCESSOR - STORAGE AND MEMORY CHOICE

#### Choose your performance spec based around the powerful Intel<sup>®</sup> i7 Core<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.


A standard warranty of 12 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT500-24T with Intel<sup>®</sup> i7 Core<sup>™</sup> CPU

23.6in Medical Cart Computer with capacitive touch LCD, Intel® 10th Gen i7 Core™ processor, medical grade AC/DC adapter. Supplied with 3 × MT202 Batteries.





\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.

#### MT500-24T - i9 PROCESSOR - STORAGE AND MEMORY CHOICE



#### Choose your performance spec based around the powerful Intel<sup>®</sup> i9 Core<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.

A standard warranty of 12 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT500-24T with Intel<sup>®</sup> i9 Core<sup>™</sup> CPU

23.6in Medical Cart Computer with capacitive touch LCD, Intel<sup>®</sup> 10th Gen i9 Core™ processor, medical grade AC/DC adapter. Supplied with 3 × MT202 Batteries.



| Window                         | rs11 24in             |         |                   |                      |                       |
|--------------------------------|-----------------------|---------|-------------------|----------------------|-----------------------|
| 300 m                          | -                     | HDD     | <u>[00000000]</u> | WARRANTY             |                       |
| Part Number                    | Operating System      | Storage | RAM               | Standard<br>Warranty | Extended<br>Warranty* |
| MT500-24T-584T90-X- <b>495</b> | Specify when ordering | 256GB   | 8GB               | 12 months            | 60 months             |
| MT500-24T-584T90-X- <b>595</b> | Specify when ordering | 256GB   | 16GB              | 12 months            | 60 months             |

\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.

512GB

16GB

Specify when ordering

MT500-24T-584T90-X-5A5

60 months

12 months





# **MEDICAL AIO**

### **BATTERY POWERED / 22IN**





|   | Joseph W  | _            |           |  | A                                   |     | Arture 💬        |             |             |
|---|---|--------------|-----------|--|-------------------------------------|-----|-----------------|-------------|-------------|
| 2 | Thermore Profession   |              |           |  |                                     |     | Basely of       |             | -           |
| • | Lauran  | Dark.        | -         |  | 8/96/1903 /6.04<br>(0.06.0003 /6.04 |     | Francisc Mark - | 7           |             |
|   |   |              |           |  |                                     | -   | 1000            | (           | 24/7        |
|   | Book Harry Party  | ARRAY        | strenest. | Climited   | DALE ROAD                           |     |                 |             |             |
|   | COLUMNICON  |              | metral    |  | 2010/00/001                         | 1   | _               |             |             |
|   | New Yorghand (1985)   |              |           |  | acris 610 (440                      |     | _               | NC          |             |
|   | Box Brook (107) Dark (1973)   | · add an one |           |  |                                     | 4   |                 | HOT-S       | WAPPA       |
| 0 | man for many party of the   |              | with m    |  |                                     |     |                 | P           | OWER        |
|   | The second second   |              | -         | And the state of the state   | P.76207.500                         | 1.  |                 |             |             |
|   | Assembland  |              |           | and in such as the   | 10.10.001.000                       | *   | -               | Contract of | 10000       |
|   | while these links (new particip   | · LT periet  | 10-00     |  | monant (im)                         | 1   | 目的時             |             |             |
|   |   |              | +10       |  | The second second                   |     | - 816           | 1 日日        | <b>#</b> 10 |
|   | Automation in the second se |              |           |  | Descenario                          | 100 |                 |             |             |
|   | Land Point Land Point Land Point Land   | see.cl       | RINNET.   |  | 100x101104                          | <., | 田田              | 458         | 4-5         |
|   | hausenin  |              | read      |  |                                     | 1   |                 |             |             |
|   | and the second second   | -            | ++21      | And the second s |                                     |     |                 |             |             |
|   | NEX Contrained  |              |           |  |                                     |     | 11113           | 1005-5      | 0.032       |

#### STATE-OF-THE-ART TOUCH SCREEN



10-point multi touch capacitive type screens as standard!

#### CHARGER DOCK (available separately)



Charge up to 6 Li-ion battery packs simultaneously!

#### PRODUCT CODE


## $\rm MT500\mathchar`22T$ Battery powered 22 in AlO touch screen medical grade monitor/PC

The Freeway Med-Tech MT500-22T Battery Powered All-In-One Monitor/PC offers fully mobile computing with its powerful, hot-swappable rechargeable battery packs. Options for 1, 2 or 3 Lithium-ion batteries allow for either an emergency power back up, or totally wire-free operation. Also features a handy built-in reading light.

#### DIMENSIONS

Height = 345.9mm Width = 516.9mm Depth = 40.4mm

#### PRODUCT ELEVATIONS




#### KEY FEATURES

- Uses up to 3 Lithium-ion batteries for a full shift of mobile operation
- No need to be near mains power
- Intel Core-i5/7/9 processors
- Runs Microsoft® Windows® / Linux / Igel
- DC outputs can power PC peripherals and other medical equipment
- High contrast 22" capacitive-type touch screen
- Slim fanless design
- UL60601 certified with anti-microbial enclosure
- Withstands common medical environment cleaning chemicals<sup>\*</sup>



REAR

100x100 VESA mounting



Uses up to 3 Li-ion batteries



Water resistant enclosures

FREEWAY ● U Med-Tech ● U

The screen and rear enclosure are IP rated against dust and moisture ingress, ensuring easy cleaning and disinfection\*.

\*See pages 194/5 for detailed information on cleaning chemicals and procedures.

| ÷ | <br>١. |   | 1 |
|---|--------|---|---|
| L |        | e | L |
|   |        |   |   |

Choice of processor

Modern Intel<sup>®</sup> Core-i7/9 range of processors to choose from.



**Optional DC-out** Can power PC peripherals and other medical equipment.



Battery status made easy

Front facing LED battery indicators offer feedback on the health of each battery.



Easily hot-swap battery packs in a matter of seconds




Clear battery status LEDs



The **OPTIONAL** DC-out can power PC peripherals!



Moisture resistant medical-grade front panel



A choice of 6 to 10 cores of Intel processing power.



#### Windows OS

IoT Enterprise version available for pre-install with or without license.

Linux/lgel operating systems can also be installed.

Industry standard OS for medical software and systems.

## 

#### TECHNICAL SPECIFICATIONS

| System                  |   |       |
|-------------------------|---|-------|
| CPU                     | Intel <sup>®</sup> Core™ i5-10500T, 2.3 GHz (up to 3.8GHz) - <b>6 core</b><br>Intel <sup>®</sup> Core™ i7-10700T, 2.0 GHz (up to 4.5GHz) - <b>8 core</b><br>Intel <sup>®</sup> Core™ i9-10900T, 1.9 GHz (up to 4.6GHz) - <b>10 core</b> | intel |
| RAM                     | 8GB to 64GB   |       |
| Storage                 | 256Gb to 4TB Flash (mPCle NVMe type SSD)  |       |
| Operating System        | Microsoft® Windows®/Linux/Igel - specify pre-install if required  |       |
| Display                 | 21.5in capacitive touch screen  |       |
| Display resolution      | 1920×1080   |       |
| Trusted platform module | TPM 2.0   |       |
| Reading light           | LED reading light × I   |       |
| Microphone and speaker  | Built-in microphones and speaker  |       |
| Network Interface       |   |       |
| WLAN                    | Ethernet 10/100/1000 MB Base-T LAN; Wi-Fi 802.11ax, 2.4GHz/5GHz dual band   |       |
| Bluetooth               | Bluetooth 5.1   |       |
| I/O Ports               |   |       |
| USB Ports               | USB 2.0 x 2 and USB 3.0 x 4   |       |
| COM Port                | 2   |       |
| HDMI-out (1.4a)         | I   |       |
| Audio Jack              | I   |       |
| Ethernet                | RJ45 connector for ethernet x I   |       |
| DC-in                   | I   |       |
| DC-out (optional)       | 12V × 1, 15V × 1, 19V × 1   |       |

| Mechanical/Environmental           |  |
|------------------------------------|--|
| Fan/Fanless                        | Fanless  |
| AC/DC Adaptor                      | Input: 100 – 240V AC; Output: 19V DC, 6.31A  |
| Battery Pack                       | MT202 Li-ion battery; 85Wh, 7800mAh x 3 (optional)   |
| Enclosure                          | ABS + PC plastics, anti-microbial enclosure  |
| Dimensions $(H \times W \times D)$ | 345.9 x 516.9 x 40.4mm   |
| Weight                             | 7.3kg (without battery) - 8.7kg (with 3 batteries)   |
| VESA-compliant mounting            | 100mm × 100mm VESA standard  |
| Water Resistance                   | Front panel: IP65; Enclosure: IPX2   |
| Regulatory                         | ANSI/AAMI ES60601-1, IEC60601-1, IEC60601-1-2, FCC Part 18, FCC Part 15 Class B, GB<br>17625.1, GB 4943.1, GB/T 9254, CE-EMC, CE-RED, RCM, CCC |
| Major options                      |  |
| Camera                             | Full-HD front camera   |
| NFC/RFID reader                    | Dual frequency, reads both 125KHz and 13.56MHz credentials   |
| Smart Card/CAC Reader              | Full-slot, reads ISO 7816T=0,T=1; 1.8/3/5V smart card  |
|                                    |  |



Optional Imprivata certified RFID reader



#### Faster processors than our competitors!

Our Intel® Core i5 CPU is effectively 30% faster in real-world benchmark tests.

| *Shorter bars are better  |          |                     |                        |
|---------------------------|----------|---------------------|------------------------|
| Our Competitors' i5 CPU   |          | Competitors'<br>CPU | Med-Tech CPU           |
| Freeway Med-Tech's i5 CPU | <b>v</b> | STEE ALLON          | 2011 Autor 2017 / 1285 |

#### MT500-22T ACCESSORIES (available separately)



#### MT500-22T - PENTIUM™ PROCESSOR - STORAGE AND MEMORY CHOICE

#### Choose your performance spec based around the Intel<sup>®</sup> Pentium<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.


A standard warranty of 12 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT500-22T with Intel<sup>®</sup> Pentium<sup>™</sup> CPU

21.5in Medical Cart Computer with capacitive touch LCD, Intel<sup>®</sup> 10th Gen Pentium™ processor, medical grade AC/DC adapter.





\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.

512GB

16GB

12 months

60 months

Specify when ordering

MT500-22T-582TP0-X-5A5

#### MT500-22T - i5 PROCESSOR - STORAGE AND MEMORY CHOICE

### 

#### Choose your performance spec based around the powerful Intel<sup>®</sup> i5 Core<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.

A standard warranty of I2 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT500-22T with Intel<sup>®</sup> i5 Core<sup>™</sup> CPU

21.5in Medical Cart Computer with capacitive touch LCD, Intel<sup>®</sup> 10th Gen i5 Core™ processor, medical grade AC/DC adapter:





| () and () |                       | HDD     | [0000000] |                      |                       |
|--|-----------------------|---------|-----------|----------------------|-----------------------|
| Part Number  | Operating System      | Storage | RAM       | Standard<br>Warranty | Extended<br>Warranty* |
| MT500-22T-582T50-X <b>-495</b>   | Specify when ordering | 256GB   | 8GB       | 12 months            | 60 months             |
| MT500-22T-582T50-X- <b>595</b>   | Specify when ordering | 256GB   | I 6GB     | 12 months            | 60 months             |
| MT500-22T-582T50-X- <b>5A5</b>   | Specify when ordering | 512GB   | I 6GB     | 12 months            | 60 months             |

\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.

#### MT500-22T - i7 PROCESSOR - STORAGE AND MEMORY CHOICE

#### Choose your performance spec based around the powerful Intel<sup>®</sup> i7 Core<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.

A standard warranty of 12 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT500-22T with Intel<sup>®</sup> i7 Core<sup>™</sup> CPU

21.5in Medical Cart Computer with capacitive touch LCD, Intel® 10th Gen i7 Core™ processor, medical grade AC/DC adapter. Supplied with 3 × MT202 Batteries.





| 0 and                          |                       | HDD     | <u>{ </u> |                      | WARRANTY<br>WARRANTY  |
|--------------------------------|-----------------------|---------|-----------|----------------------|-----------------------|
| Part Number                    | Operating System      | Storage | RAM       | Standard<br>Warranty | Extended<br>Warranty* |
| MT500-22T-582T70-X- <b>495</b> | Specify when ordering | 256GB   | 8GB       | 12 months            | 60 months             |
| MT500-22T-582T70-X- <b>595</b> | Specify when ordering | 256GB   | 16GB      | 12 months            | 60 months             |
| MT500-22T-582T70-X- <b>5A5</b> | Specify when ordering | 512GB   | 16GB      | 12 months            | 60 months             |

\*Extended Warranty available as a cost option, please enquire for prices at time of order: Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.

#### MT500-22T - i9 PROCESSOR - STORAGE AND MEMORY CHOICE



Choose your performance spec based around the powerful Intel<sup>®</sup> i9 Core<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.

A standard warranty of I2 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT500-22T with Intel<sup>®</sup> i9 Core<sup>™</sup> CPU

21.5in Medical Cart Computer with capacitive touch LCD, Intel<sup>®</sup> 10th Gen i9 Core™ processor, medical grade AC/DC adapter: Supplied with 3 × MT202 Batteries.





| ·                              |                       | HDD     | <u>{ 00000000 }</u> | WARRANTY<br>WARRANTY |                       |
|--------------------------------|-----------------------|---------|---------------------|----------------------|-----------------------|
| Part Number                    | Operating System      | Storage | RAM                 | Standard<br>Warranty | Extended<br>Warranty* |
| MT500-22T-582T90-X <b>-495</b> | Specify when ordering | 256GB   | 8GB                 | 12 months            | 60 months             |
| MT500-22T-582T90-X- <b>595</b> | Specify when ordering | 256GB   | 16GB                | 12 months            | 60 months             |
| MT500-22T-582T90-X- <b>5A5</b> | Specify when ordering | 512GB   | 16GB                | 12 months            | 60 months             |

\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.





# **MEDICAL AIO**

### MAINS POWERED / 24IN



### MT400-24T - AIO MAINS POWERED 24IN MEDICAL PC



|                                   | oh Webb +++        | A CONTRACTOR OF THE OWNER OWNER OF THE OWNER |   |                                      |       | Adam 🖂             |                |
|-----------------------------------|--------------------|--|---|--------------------------------------|-------|--------------------|----------------|
| Therefore a                       | Real Property lies |  |   |                                      |       | Aparts of          |                |
| Lauren                            | Deprint 1          |  | Gaugine fair -  | 10706-2008 10.04<br>102706-2008 1028 |       | Francisco Martin - |                |
| Contractory in                    |                    |  |   | Dark Horse                           |       | -                  |                |
| CONTRACTOR                        | (amaid             | metted   | Constant of the local diversion of the local | mile-001 701                         | 1     | 1                  |                |
|                                   | . 144.4            |  |   | increased into the                   | 5     |                    |                |
| And Amount of Card Area           | · Add over the     | ****   |   | Advantation of the                   |       |                    |                |
| and in the section of the         | • m/ae             | mile   |   |                                      | 1     |                    |                |
| There are a second second         |                    | -  | Acres 101-101-001-010   | printer and                          | -     | _                  |                |
| Rannin Card                       |                    | 12-010   |   | 1010,001 000                         | -     |                    |                |
| With Direction Carls Court (1996) |                    | +10  |   | In the second view.                  | · · · | Date for ministry  |                |
|                                   | • 18 (Arrist)      |  |   | Desaration                           | 1.00. | -                  | and the second |
| a sectore a                       | Jens/              | MINIST   |   | distant of 1                         | 1     |                    | r à            |
| Catalogue Antonio                 | # identify         | +48  |   |                                      | 1     |                    |                |
| and and a second                  | -                  | 6823   | And the second second   | Contraction of the                   |       |                    |                |
| HR Danase                         |                    |  |   |                                      | 4000  |                    |                |

#### STATE-OF-THE-ART TOUCH SCREEN



10-point multi touch capacitive type screens as standard!

#### MAINS POWERED (iWOW required to be plugged-in)



#### PRODUCT CODE


## $\rm MT400\text{-}24T$ Mains powered 24in AlO touch screen medical grade PC

The Freeway Med-Tech MT400-24T Mains Powered All-In-One Monitor/PC offers the same technical specification and features as our battery powered AlO model, just with the need for a permanent 240V mains supply. For use where an IWOW will be predominately used in a fixed location.

#### DIMENSIONS

Height = 370.9mm Width = 564.4mm Depth = 41.2mm

#### PRODUCT ELEVATIONS



#### KEY FEATURES

- Intel Core-i5/7/9 processors
- Runs Microsoft® Windows® / Linux / Igel
- High contrast 24" capacitive-type touch screen
- Slim fanless design
- UL60601 certified with anti-microbial enclosure
- Withstands common medical environment cleaning chemicals\*


#### MT400-24T - AIO MAINS POWERED 24IN MEDICAL PC

### FREEWAY ● Ů Med-Tech ● ●





100x100 VESA mounting





Water resistant enclosures

The screen and rear enclosure are IP rated against dust and moisture ingress, ensuring easy cleaning and disinfection\*.

\*See pages 194/5 for detailed information on cleaning chemicals and procedures.


| intel   |
|---------|
| in neer |

Choice of processor Modern Intel Core-i5/7/9 range of processors to choose from.



Mains powered Requires a permanent 240V mains outlet for use.

### MT400-24T - AIO MAINS POWERED 24IN MEDICAL PC




Anti-microbial enclosure resists bacteria transmission



Built-in speakers and clear easy-to-use function buttons located on the underside of the monitor



Moisture resistant medical-grade front panel



A choice of 6 to 10 cores of Intel processing power.



Windows OS

IoT Enterprise version available for pre-install with or without license.

Linux/Igel operating systems can also be installed.

Industry standard OS for medical software and systems.



#### **TECHNICAL SPECIFICATIONS**

| System                              |   |
|-------------------------------------|---|
| CPU                                 | Intel <sup>®</sup> Core™ i5-10500T, 2.3 GHz (up to 3.8GHz) - <b>6 core</b><br>Intel <sup>®</sup> Core™ i7-10700T, 2.0 GHz (up to 4.5GHz) - <b>8 core</b><br>Intel <sup>®</sup> Core™ i7-10900T, 1.9 GHz (up to 4.6GHz) - <b>10 core</b> |
| RAM                                 | 8GB to 64GB   |
| Storage                             | 256Gb to 4TB Flash (mPCle NVMe type SSD)  |
| Operating System                    | Microsoft® Windows®/Linux/Igel - specify pre-install if required  |
| Display                             | 23.8in capacitive touch screen  |
| Display resolution                  | 1920×1080   |
| Trusted platform module             | TPM 2.0   |
| Battery Pack                        | Optional integrated UPS battery × 1   |
| Buttons                             | I power and 4 programmable buttons  |
| Microphone and speaker              | Built-in microphones and speaker  |
| Network Interface                   |   |
| WLAN                                | Wi-Fi 802.1 Iax, 2.4GHz/5GHz dual band  |
| Bluetooth                           | Bluetooth 5.1 LE  |
| I/O Ports                           |   |
| USB Ports                           | USB 3.0 x 4 (ESD protection: ±17KV by air, ±12KV by contact)<br>USB 2.0 x 2 (ESD protection: ±18KV by air, ±12KV by contact)  |
| COM Port                            | 3   |
| HDMI-out (1.4a)                     | I (ESD protection: $\pm 17KV$ by air, $\pm 12KV$ by contact)  |
| Audio Jack                          | 1   |
| Ethernet                            | RJ45 connector $\times$ 2 (ESD protection: $\pm 30 \text{KV}$ by air; $\pm 30 \text{KV}$ by contact)  |
| DC-in                               | 1   |
| Potential Equalization<br>Conductor | l (optional)  |

| Mechanical/Environmental           |   |
|------------------------------------|---|
| Fan/Fanless                        | Fanless   |
| AC/DC Adaptor                      | Input: 100 – 240V AC; Output: 19V DC, 6.31A   |
| Enclosure                          | Aluminum alloy, antimicrobial enclosure   |
| Dimensions $(H \times W \times D)$ | 370.9 x 564.4 x 41.2mm  |
| Weight                             | 8kg   |
| VESA-compliant mounting            | 100mm × 100mm VESA standard   |
| Water Resistance                   | Front panel: IP65; Enclosure: IPX2  |
| Regulatory                         | ANSI/AAMI ES60601-1, IEC60601-1, IEC60601-1-2, FCC Part 18, FCC Part 15 Class B, GB<br>17625.1, GB 4943.1, GB/T 9254, CE-EMC, CE-RED, Energy Star 8.0, RCM, CCC |
| Major options                      |   |
| Camera                             | Full-HD front camera  |
| NFC/RFID reader                    | HF 13.56MHz, ISO standard 15693, 14443A(B) & 18000-3 mode-1, or dual frequency, reads<br>both 125KHz and 13.56MHz credentials                                   |
| Smart Card/CAC Reader              | Full-slot, reads ISO 7816 T=0, T=1; 1.8/3/5V smart card   |



Optional Imprivata certified RFID reader



#### Faster processors than our competitors!

Our Intel<sup>®</sup> Core i5 CPU is effectively 30% faster in real-world benchmark tests.



#### MT400-24T - PENTIUM™ PROCESSOR - STORAGE AND MEMORY CHOICE

#### Choose your performance spec based around the Intel<sup>®</sup> Pentium<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.


A standard warranty of 12 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT400-24T with Intel<sup>®</sup> Pentium<sup>™</sup> CPU

23.6in Medical Cart Computer with capacitive touch LCD, Intel<sup>®</sup> 10th Gen Pentium™ processor, medical grade AC/DC adapter.





\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.

#### MT400-24T - i5 PROCESSOR - STORAGE AND MEMORY CHOICE

#### FREEWAY ●●● Med-Tech●●●

#### Choose your performance spec based around the powerful Intel<sup>®</sup> i5 Core<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.

A standard warranty of I2 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT400-24T with Intel<sup>®</sup> i5 Core<sup>™</sup> CPU

23.6in Medical Cart Computer with capacitive touch LCD, Intel<sup>®</sup> 10th Gen i5 Core™ processor, medical grade AC/DC adapter:





|                                |                       | HDD     | 2000000005 | WARRANTY]            | WARRANTY              |
|--------------------------------|-----------------------|---------|------------|----------------------|-----------------------|
| Part Number                    | Operating System      | Storage | RAM        | Standard<br>Warranty | Extended<br>Warranty* |
| MT400-24T-504T5-X- <b>C495</b> | Specify when ordering | 256GB   | 8GB        | 12 months            | 60 months             |
| MT400-24T-504T5-X- <b>C595</b> | Specify when ordering | 256GB   | 16GB       | 12 months            | 60 months             |
| MT400-24T-504T5-X- <b>C5A5</b> | Specify when ordering | 512GB   | 16GB       | 12 months            | 60 months             |

\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.

#### MT400-24T - i7 PROCESSOR - STORAGE AND MEMORY CHOICE

#### Choose your performance spec based around the powerful Intel<sup>®</sup> i7 Core<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.


A standard warranty of 12 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT400-24T with Intel<sup>®</sup> i7 Core<sup>™</sup> CPU

23.6in Medical Cart Computer with capacitive touch LCD, Intel® 10th Gen i7 Core™ processor, medical grade AC/DC adapter.





\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.

512GB

16GB

12 months

60 months

Specify when ordering

MT400-24T-504T7-X-C5A5

#### Choose your performance spec based around the powerful Intel<sup>®</sup> i9 Core<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.

A standard warranty of I2 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT400-24T with Intel<sup>®</sup> i9 Core<sup>™</sup> CPU

23.6in Medical Cart Computer with capacitive touch LCD, Intel<sup>®</sup> 10th Gen i9 Core™ processor, medical grade AC/DC adapter.





|                                |                       |         |      | •                    | •                     |
|--------------------------------|-----------------------|---------|------|----------------------|-----------------------|
| Part Number                    | Operating System      | Storage | RAM  | Standard<br>Warranty | Extended<br>Warranty* |
| MT400-24T-504T9-X- <b>C495</b> | Specify when ordering | 256GB   | 8GB  | 12 months            | 60 months             |
| MT400-24T-504T9-X- <b>C595</b> | Specify when ordering | 256GB   | 16GB | 12 months            | 60 months             |
| MT400-24T-504T9-X- <b>C5A5</b> | Specify when ordering | 512GB   | 16GB | 12 months            | 60 months             |

\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.





### **MEDICAL AIO**

MAINS POWERED / 27IN





|  | h Webb   | A CONTRACTOR OF THE OWNER OWNER OF THE OWNER |   |                                     |      | Adam 🖂              |                |
|--|--|--|---|-------------------------------------|------|---------------------|----------------|
| Batters  | Base of the local division of the local divi |  |   |                                     |      | Reads of            |                |
| Lauren   | ingenter 1   |  | Canadian Take<br>Restored See   | 8/16/2018 10.04<br>82/16/2018 10:08 |      | Francisco Maria -   |                |
| Contractory and  |  |  |   | DATE HINTER                         |      | -                   |                |
| CONSTRUCTOR  | (amaid   | metted   | Constant of the local division of the local | ACTIVATION AND                      | 1    |                     |                |
|  |  |  |   | increased into a                    | 5    |                     |                |
| Red Brown (at 12st) ARC)   | · all or yes   | ****   |   | Address of the second               |      |                     |                |
| and in the section of the  | • mile   | mile   |   |                                     | 1    |                     |                |
|  |  | -  | Acres 101-101-000-000   | printer and                         |      |                     |                |
| Rates Card   |  | 10.000   |   | 10.00.000                           |      |                     |                |
| Without Darks, Clauser, Statistics   |  | +15  |   | and and the                         | ×.   | Date for married of |                |
|  | · 18 (4-14)  |  |   | percenter.                          | 1.00 |                     | and the second |
| Contraction of the local division of the loc | anna)  | MINIST   |   | descent tor                         | 2    |                     |                |
| Catalitation .   |  | ++delt   |   | 10400-0000 W                        | 1    |                     |                |
| and and a second   | -  | 68473  | And shares and the  | and the second second               |      |                     |                |
| His Department   |  |  |   |                                     |      |                     |                |

#### STATE-OF-THE-ART TOUCH SCREEN



10-point multi touch capacitive type screens as standard!

#### MAINS POWERED (iWOW required to be plugged-in)



#### PRODUCT CODE


#### $\rm MT400\text{-}27T$ Mains powered 27in AlO touch screen medical grade PC

The Freeway Med-Tech MT400-27T Mains Powered All-In-One Monitor/PC offers the same technical specification and features as our battery powered AlO model, just with the need for a permanent 240V mains supply. For use where an IWOW will be predominately used in a fixed location.

#### DIMENSIONS

Height = 411.8mm Width = 639.1mm Depth = 45mm

#### PRODUCT ELEVATIONS



#### KEY FEATURES

- Intel Core-i5/7/9 processors
- Runs Microsoft® Windows® / Linux / Igel
- High contrast 27" capacitive-type touch screen
- Slim fanless design
- UL60601 certified with anti-microbial enclosure
- Withstands common medical environment cleaning chemicals\*










100×100 VESA mounting



REAR



Water resistant enclosures

The screen and rear enclosure are IP rated against dust and moisture ingress, ensuring easy cleaning and disinfection\*.


\*See pages 194/5 for detailed information on cleaning chemicals and procedures.

| inte |  |  |   |
|------|--|--|---|
|      |  |  | ł |
|      |  |  | U |


Choice of processor Modern Intel Core-i5/7/9 range of processors to choose from.



#### Mains powered Requires a permanent 240V mains outlet for use.




Anti-microbial enclosure resists bacteria transmission



Built-in speakers and clear easy-to-use function buttons located on the underside of the monitor



Moisture resistant medical-grade front panel



A choice of 6 to 10 cores of Intel processing power.



Windows OS

IoT Enterprise version available for pre-install with or without license.

Linux/Igel operating systems can also be installed.

Industry standard OS for medical software and systems.

### FREEWAY ● Ů ● M e d - T e c h ● ● ●

#### TECHNICAL SPECIFICATIONS

| System                              |   |  |  |  |
|-------------------------------------|---|--|--|--|
| CPU                                 | Intel® Core™ i5-10500T,2.3 GHz (up to 3.8GHz) - 6 core         Intel® Core™ i7-10700T,2.0 GHz (up to 4.5GHz) - 8 core         Intel® Core™ i7-10700T,1.9 GHz (up to 4.6GHz) - 10 core |  |  |  |
| RAM                                 | 8GB to 64GB   |  |  |  |
| Storage                             | 256Gb to 4TB Flash (mPCIe NVMe type SSD)  |  |  |  |
| Operating System                    | Microsoft® Windows®/Linux/Igel - specify pre-install if required  |  |  |  |
| Display                             | 27in capacitive touch screen  |  |  |  |
| Display resolution                  | 1920×1080 (optional 3840×2160)  |  |  |  |
| Trusted platform module             | TPM 2.0   |  |  |  |
| Battery Pack                        | Optional integrated UPS battery × I   |  |  |  |
| Buttons                             | I power and 4 programmable buttons  |  |  |  |
| Microphone and speaker              | Built-in microphones and speaker  |  |  |  |
| Network Interface                   |   |  |  |  |
| WLAN                                | Wi-Fi 802.1 Lax, 2.4GHz/5GHz dual band  |  |  |  |
| Bluetooth                           | Bluetooth 5.1 LE  |  |  |  |
| I/O Ports                           |   |  |  |  |
| USB Ports                           | USB 3.0 $\times$ 4 (ESD protection: ±17KV by air, ±12KV by contact)<br>USB 2.0 $\times$ 2 (ESD protection: ±18KV by air, ±12KV by contact)  |  |  |  |
| COM Port                            | 3   |  |  |  |
| HDMI-out (1.4a)                     | I (ESD protection: ±17KV by air, ±12KV by contact)  |  |  |  |
| Audio Jack                          | I   |  |  |  |
| Ethernet                            | RJ45 connector x 2 (ESD protection: $\pm$ 30KV by air; $\pm$ 30KV by contact)   |  |  |  |
| DC-in                               | I   |  |  |  |
| Potential Equalization<br>Conductor | l (optional)  |  |  |  |

| Mechanical/Environmental           |   |
|------------------------------------|---|
| Fan/Fanless                        | Fanless   |
| AC/DC Adaptor                      | Input: 100 – 240V AC; Output: 19V DC, 6.31A   |
| Enclosure                          | Aluminum alloy, antimicrobial enclosure   |
| Dimensions $(H \times W \times D)$ | 411.8 × 639.1 × 45mm  |
| Weight                             | 10.5kg  |
| VESA-compliant mounting            | 100mm × 100mm VESA standard   |
| Water Resistance                   | Front panel: IP65; Enclosure: IPX2  |
| Regulatory                         | ANSI/AAMI ES60601-1, IEC60601-1, IEC60601-1-2, FCC Part 18, FCC Part 15 Class B, GB<br>17625.1, GB 4943.1, GB/T 9254, CE-EMC, CE-RED, Energy Star 8.0, RCM, CCC |
| Major options                      |   |
| Camera                             | Full-HD front camera  |
| NFC/RFID reader                    | HF 13.56MHz, ISO standard 15693, 14443A(B) & 18000-3 mode-1, or dual frequency, reads<br>both 125KHz and 13.56MHz credentials                                   |
| Smart Card/CAC Reader              | Full-slot, reads ISO 7816 T=0, T=1; 1.8/3/5V smart card   |



Optional Imprivata certified RFID reader



#### Faster processors than our competitors!

Our Intel<sup>®</sup> Core i5 CPU is effectively 30% faster in real-world benchmark tests.



#### MT400-27T - PENTIUM™ PROCESSOR - STORAGE AND MEMORY CHOICE

#### Choose your performance spec based around the Intel<sup>®</sup> Pentium<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.


A standard warranty of 12 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT400-27T with Intel<sup>®</sup> Pentium<sup>™</sup> CPU

27in Medical Cart Computer with capacitive touch LCD, Intel<sup>®</sup> 10th Gen Pentium™ processor, medical grade AC/DC adapter.





\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.



#### Choose your performance spec based around the powerful Intel<sup>®</sup> i5 Core<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.

A standard warranty of I2 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT400-27T with Intel<sup>®</sup> i5 Core<sup>™</sup> CPU

27in Medical Cart Computer with capacitive touch LCD, Intel<sup>®</sup> 10th Gen i5 Core™ processor, medical grade AC/DC adapter.





| () and a second |                       | HDD     |      |                      |                       |
|---|-----------------------|---------|------|----------------------|-----------------------|
| Part Number   | Operating System      | Storage | RAM  | Standard<br>Warranty | Extended<br>Warranty* |
| MT400-27T-507T5-X- <b>C495</b>  | Specify when ordering | 256GB   | 8GB  | 12 months            | 60 months             |
| MT400-27T-507T5-X- <b>C595</b>  | Specify when ordering | 256GB   | 16GB | 12 months            | 60 months             |
| MT400-27T-507T5-X- <b>C5A5</b>  | Specify when ordering | 512GB   | 16GB | 12 months            | 60 months             |

\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.

#### MT400-27T - i7 PROCESSOR - STORAGE AND MEMORY CHOICE

#### Choose your performance spec based around the powerful Intel<sup>®</sup> i7 Core<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.


A standard warranty of 12 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT400-27T with Intel<sup>®</sup> i7 Core<sup>™</sup> CPU

27in Medical Cart Computer with capacitive touch LCD, Intel® 10th Gen i7 Core™ processor, medical grade AC/DC adapter.





\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.

512GB

16GB

12 months

60 months

Specify when ordering

MT400-27T-507T7-X-C5A5



#### Choose your performance spec based around the powerful Intel<sup>®</sup> i9 Core<sup>™</sup> central processing unit.

Delivered ready to switch on, each Freeway Med-Tech AIO monitor/PC is pre-installed with an OS ready to enter your license details.

A standard warranty of I2 months from date of purchase covers any faulty components or workmanship with the option to extend this by an extra 48 months to 5 years in total from date of purchase.

Please quote the correct part number opposite when ordering as all units are custom built.

#### MT400-27T with Intel<sup>®</sup> i9 Core<sup>™</sup> CPU

27in Medical Cart Computer with capacitive touch LCD, Intel<sup>®</sup> 10th Gen i9 Core™ processor, medical grade AC/DC adapter.





| () and () |                       | HDD     | <u>`````````````````````````````````````</u> | WARRANTY<br>WARRANTY | WARRANTY              |
|--|-----------------------|---------|--|----------------------|-----------------------|
| Part Number  | Operating System      | Storage | RAM  | Standard<br>Warranty | Extended<br>Warranty* |
| MT400-27T-507T9-X- <b>C495</b>   | Specify when ordering | 256GB   | 8GB  | 12 months            | 60 months             |
| MT400-27T-507T9-X- <b>C595</b>   | Specify when ordering | 256GB   | 16GB   | 12 months            | 60 months             |
| MT400-27T-507T9-X- <b>C5A5</b>   | Specify when ordering | 512GB   | 16GB   | 12 months            | 60 months             |

\*Extended Warranty available as a cost option, please enquire for prices at time of order. Extended Warranty must be ordered at time of purchase. Extended Warranty is a 48 month extension on top of the standard 12 months offered, to provide 60 months from date of first purchase.





## **MEDICAL MONITOR**

#### **BATTERY POWERED / 24IN**



The Freeway Med-Tech battery powered monitor will power a Dell MFF PC and/or peripheral devices!

No need for large expensive 'car battery' style power supplies.

#### 3 x DC outs - 12, 15 & 19V

The 3 different output voltages give flexibility to power up various popular add-on devices.

Example opposite shows use of the 12, 15 & 19V DC outputs.





### 🕸. ZEBRA

#### An important peripheral

No need to dock and separately charge this mobile label printer. It is kept topped up all day via the monitor's battery packs.



#### A full speed workstation

When our MT700 Monitor is used on a mobile workstation, all the power that is required to operate a MFF PC comes direct from the Monitor's DC outs! Popular Dell, HP and Lenovo DC-in voltages supported.



#### **Medical monitors**

The 15V output from the MT700-24T can also power important pieces of equipment like these Vital Signs Monitors.



# The MT700 Monitor offers low 'cost to entry' for mobile go-anywhere workstations as well as a lower lifecycle cost<sup>\*</sup>.



#### Already have the PC hardware?

By utilising an existing and suitable Dell MFF PC, the MT700 immediately offers mobile computing together with the benefit of being able to update the PC at a later date relatively inexpensively compared with an AIO system!



Initial MT700 purchase

Year 0

\*Compared with all-in-one monitor/PCs and/or mobile workstations using large dedicated battery systems.

### LOWER LIFECYCLE COST COMPARED TO AIO / DEDICATED BATTERY - MT700-24T FREEWAY



No dedicated expensive battery packs

#### Note - All batteries have a performance lifespan

This is why we utilise the highest quality lithium cells from a brand leader and package them up into small individual 90Wh battery packs. The replacement and servicing cost for these smaller units is much lower than older large dedicated battery setups.





|   | Joseph W   |               | A CONTRACTOR OF THE OWNER OF THE |  |                           |     | Arten 😒               | Т      |         |
|---|--|---------------|--|--|---------------------------|-----|-----------------------|--------|---------|
| 9 | Televiser Police   | Alexandra rok |  |  |                           |     | Baselin of            | (`     | 24/7    |
| • | identity   | Darm 1        | -  | Constant bits<br>Reconstition              | BURG 101 5.5              |     | From a refer Manual - |        | · 📔 🖌   |
|   | Ward Hall Dalls  |               |  | Canadral                                   | DALE ROUTE                |     | 10102                 | NO     | N-STOP  |
|   | 0006894508   | ARRAT         | streng-str.  |  | 2010/001 101              |     |                       |        | WAPPABL |
|   | Name Incompletent (1980)   | # 14 wh       | 10 M al  |  |                           |     |                       | P      | OWER    |
|   |  | -             | 4448   | And the sub-                               | arrs 221 949              |     |                       |        |         |
|   | Bed Brook (10712-04875   |               |  |  | Achieved for              | ÷ . |                       |        |         |
|   | max for managing price   |               | 10.111 m   |  |                           |     |                       |        |         |
|   |  |               | -  | And the state of the local division of the | P(76.247.748              | 1.1 |                       |        |         |
|   | Assemblish   |               |  |  | 10,740,7004,7017          | *   | ARR OT                | -      | 1000    |
|   | strate blood bols Court (1980)   | · LTurnet     | 10-001   |  |                           | 1   | 1111日                 |        |         |
|   |  |               |  |  | monant one                |     | - BR                  |        | 品語      |
|   | And other states and s | . 18          | 100  |  |                           | -   | and the second        | ## + 9 | 14 E    |
|   | Concession in the local division of the loca |               | -  |  | DATA BOATS                | 20  | line R                | and a  | 100     |
|   | LEMPATOR .   | asset.        |  |  | 10.002.004                |     | 一题之                   | 128    |         |
|   | hatstander   | · la server l |  |  | minutes and               | 10  |                       | 1000   |         |
|   | and the second second  | -             | 0023   |  | Contraction of the second |     |                       | 198    | 198     |
|   | NEX Contrained   |               |  |  |                           |     |                       | 1102-4 |         |

#### STATE-OF-THE-ART TOUCH SCREEN



10-point multi touch capacitive type screens as standard!

#### CHARGER DOCK (available separately)



Charge up to 6 Li-ion battery packs simultaneously!


#### PRODUCT CODE **MT700-24T** Battery powered 24in touch screen medical grade monitor

The Freeway Med-Tech MT700-24T Battery Powered Monitor offers truly mobile computing for up to an entire shift due to the powerful, hot-swappable rechargeable battery packs. Available with either 1, 2 or 3 Lithiumion batteries, you choose whether you simply require emergency power back up, or a full shift of wire-free operation. Also features a handy built-in reading light.

#### DIMENSIONS

Height = 370.9mm Width = 564.4mm Depth = 41.2mm


#### PRODUCT ELEVATIONS




#### KEY FEATURES

- Uses up to 3 Lithium-ion batteries for a full shift of mobile operation
- · No need to be near mains power
- DC outputs can power a standalone micro form PC and/or computer peripherals
- High contrast 24" capacitive-type touch screen
- Slim fanless design
- UL60601 certified with anti-microbial enclosure
- Withstands common medical environment cleaning chemicals<sup>\*</sup>





100x100 VESA mounting



Uses up to 3 Li-ion batteries



Water resistant enclosures

FREEWAY ● U Med-Tech ● U

The screen and rear enclosure are IP rated against dust and moisture ingress, ensuring easy cleaning and disinfection<sup>\*</sup>.

\*See pages 194/5 for detailed information on cleaning chemicals and procedures.

| F | <b>C</b>     |
|---|--------------|
|   | <b>L</b> £££ |

**Cost effective upgrades** Separate PC allows for easy future IT upgrades.



Battery status made easy

Front facing LED battery indicators offer feedback on the health of each battery.



Easily hot-swap battery packs in a matter of seconds




Clear battery status LEDs



The monitor's DC-out can power a micro-form PC!




Moisture resistant medical-grade front panel



Anti-microbial enclosure resists bacteria transmission

#### Untreated surface

Harmful bacteria clings to the surface\*





#### TECHNICAL SPECIFICATIONS

| System                                  |   |
|---|---|
| Display                                 | 23.8in capacitive touch screen  |
| Display Resolution                      | 1920×1080   |
| Viewing Angle                           | Horizontal 89°, Vertical 89°  |
| Number of Colours                       | 16.7M   |
| Brightness                              | 250cd/m2  |
| ResponseTime                            | 16ms  |
| Control Button                          | I screen on/off button, I menu button, I auto/exit button and 2 up/down buttons |
| Reading Light                           | LED reading light × I   |
| Speaker                                 | Built-in speakers   |
| Microphone                              | Built-in microphones  |
| I/O Ports                               |   |
| USB Port                                | USB 3.0 × 6   |
| USB Port for Touch Screen<br>Connection | USB Type-B (2.0) x I  |
| USB Input Port                          | USB Type-B (2.0) $\times$ 1   |
| HDMI                                    | 1   |
| Antenna                                 | Wi-Fi passthrough × 2   |
| DC-in                                   | 1   |
| DC-out                                  | 12V x 1, 15V x 1, 19V x 1   |
| COM port                                | 2   |

| Mechanical/Environment             |  |
|------------------------------------|--|
| Fan/Fanless                        | Fanless  |
| AC/DC Adaptor                      | Input: 100 – 240V AC; Output: 19V DC, 3.78A  |
| Battery Pack                       | MT202 Li-ion battery; 90Wh, 8250mAh x 3 (optional)   |
| Enclosure                          | ABS + PC plastics, anti-microbial enclosure  |
| Dimensions $(H \times W \times D)$ | 370.9 × 564.4 × 41.2 mm  |
| Weight                             | 6.5kg (without batteries); 7.8kg (with 3 batteries)  |
| VESA-compliant mounting            | 100mm × 100mm VESA standard  |
| Regulatory                         | ANSI/AAMI ES60601-1, IEC60601-1-2, FCC Part 18, FCC Part 15 Class B, IEC 62368-1, RCM, CCC |
| Temperature                        | Operation: 0°C – 40°C; Storage: -20°C – 60°C   |
| Humidity                           | 0% – 90% non-condensing  |
| Major options                      |  |
| Camera                             | 5 megapixel front camera   |
| NFC/RFID reader                    | Dual frequency, reads both 125KHz and 13.56MHz credentials                                 |

#### MT700-24T ACCESSORIES (available separately)



MT202 Li-ion battery pack



MT202 6-gang battery charger





## **MEDICAL MONITOR**

#### MAINS POWERED / 24IN







#### STATE-OF-THE-ART TOUCH SCREEN



10-point multi touch capacitive type screens as standard!

#### MAINS POWERED (iWOW required to be plugged-in)



#### PRODUCT CODE


#### MT600-24T Mains powered 24in touch screen medical grade monitor

The Freeway Med-Tech MT600-24T Mains Powered Monitor offers the same technical specification and features as our battery powered model, just with the need for a permanent 240V mains supply. For use where an iWOW will be predominately used in a fixed location.

#### DIMENSIONS

Height = 370.9mm Width = 564.4mm Depth = 41.2mm

#### PRODUCT ELEVATIONS




#### KEY FEATURES


- · 240V mains operated
- · High contrast 24" capacitive-type touch screen
- Fanless design
- Full-HD (1920×1080) resolution
- UL60601 certified with anti-microbial enclosure
- Withstands common medical environment cleaning chemicals\*
- OPTIONAL front camera and RFID reader available

### 





100x100 VESA mounting





Water resistant enclosures

The screen and rear enclosure are IP rated against dust and moisture ingress, ensuring easy cleaning and disinfection\*.

\*See pages 194/5 for detailed information on cleaning chemicals and procedures.

Cost effective upgrades

Separate PC allows for easy future IT upgrades.



Mains powered

Requires a permanent 240V mains outlet for use.




Touch screen input

All monitors and AlO's feature state of the art 10-point multitouch capacitive type touch screens.



Moisture resistant medical-grade front panel




Built-in speakers and clear easy-to-use function buttons located on the underside of the monitor



Anti-microbial enclosure resists bacteria transmission

#### Untreated surface

Harmful bacteria clings to the surface\*





#### TECHNICAL SPECIFICATIONS

| System                                  |   |
|---|---|
| Display                                 | 23.8in capacitive touch screen  |
| Display Resolution                      | 1920×1080   |
| Viewing Angle                           | Horizontal 89°, Vertical 89°  |
| Number of Colours                       | 16.7M   |
| Brightness                              | 250cd/m2  |
| ResponseTime                            | 16ms  |
| Control Button                          | I screen on/off button, I menu button, I auto/exit button and 2 up/down buttons |
| Speaker                                 | Built-in speakers   |
| Microphone                              | Built-in microphones  |
| I/O Ports                               |   |
| USB Port                                | USB 3.0 × 6   |
| USB Port for Touch Screen<br>Connection | USB Type-B (2.0) × 1  |
| USB Input Port                          | USB Type-B (3.0) × I  |
| HDMI                                    | 1   |
| Antenna                                 | Wi-Fi passthrough x 2   |
| DC-in                                   | 1   |

| Mechanical/Environment             |  |
|------------------------------------|--|
| Fan/Fanless                        | Fanless  |
| AC/DC Adaptor                      | Input: 100 – 240V AC; Output: 19V DC, 3.78A  |
| Enclosure                          | ABS + PC plastics, anti-microbial enclosure  |
| Dimensions $(H \times W \times D)$ | 370.5 × 567 × 45.2mm   |
| Weight                             | 6.4kg  |
| VESA-compliant mounting            | 100mm × 100mm VESA standard  |
| Regulatory                         | ANSI/AAMI ES60601-1, IEC60601-1-2, FCC Part 18, FCC Part 15 Class B, IEC 62368-1, RCM, CCC |
| Temperature                        | Operation: 0°C to 40°C; Storage: -10°C to 50°C   |
| Humidity                           | 0% – 90% non-condensing  |
| Major options                      |  |
| Camera                             | 5 megapixel front camera   |
| NFC/RFID reader                    | Dual frequency, reads both 125KHz and 13.56MHz credentials                                 |





### ACCESSORIES

#### BATTERY PACKS / 6-BAY CHARGER



#### MT202 - LITHIUM-ION BATTERY PACK



#### RELATED ACCESSORIES (available separately)



MT202 6-gang battery charger

#### RELATED PRODUCTS




#### PRODUCT CODE MT202 Lithium-ion Rechargeable Battery Pack

The Freeway Med-Tech MT202 Lithium-ion battery packs are for use in our Medical Grade Monitors and AlOs and offer a voltage and capacity spec of DC10.9V 7800mAh - 85Wh. Hot-swappable and featuring internal discharge circuit protection. Charge status LEDs show 4 different stages of the power cycle to aid better charging habits. Charging is supported in-monitor, or externally in our 6-bay charger: Full charge time is approx. 4.25hrs in-monitor.

#### DIMENSIONS

Height = 148.4mm Width = 88.8mm Depth = 19.4mm

#### PRODUCT ELEVATIONS



#### KEY FEATURES

- Hot-swappable
- 4 clear charge status LEDs
- High capacity 7800mAh per pack
- · Auto short circuit protection
- · Quality Samsung cells used
- · Cloth tab for easy removal from monitor/AIO

#### MT202 - LITHIUM-ION BATTERY PACK

#### TECHNICAL SPECIFICATIONS

| Item                                      | General Parameter   | Remark   |
|---|---|--|
| Description                               | Freeway Med-Tech Li-ion rechargeable battery MT202 DC10.9V 7800mAh - 85Wh | 3S3P Assembly  |
| Cell Model                                | Samsung SDI 18650   |  |
| Typical Capacity                          | 7800mAh   |  |
| Typical Voltage                           | 10.8V   |  |
| End of Charge Voltage                     | 12.6V   |  |
| Charge Current                            | 0.2C  |  |
| Charging time                             | 4.25 hours in monitor from 10% - 90%                                      | Faster off-cart charging<br>available using our external charger |
| End discharge Voltage                     | 8.4V  |  |
| Max continuous charge                     | 3.9A  |  |
| Maximum continuous<br>Discharging Current | 10A   |  |
| Over-discharge Voltage<br>Protection cell | 2.8V  |  |
| Over-Current Discharge<br>Protection      | 13-16A  |  |
| Short circuit protection                  | With protection   |  |
| Dimension                                 | 148.4x88.8x19.4mm   |  |
| Weight                                    | 435g  |  |
| Operating Temperature Range               | Charge 0~45C, Discharge 20~60C  |  |



MT202 Batteries shown in a powered monitor MT700-24T (uses up to 3 packs).



#### SAMSUNG

**High quality components** Samsung SDI 18650 cells are used within our battery packs.



**On-battery status LEDs** Clear at-a-glance visual of battery health via four LEDs.

| 4 LEDs / | 75-100% charged |
|----------|-----------------|
| 3 LEDs / | 50-75% charged  |
| 2 LEDs / | 25-50% charged  |
| I LEDs / | 0-25% charged   |



#### MT202 - 6-BAY SMART CHARGER



#### RELATED PRODUCTS (available separately)





FREEWAY 252 MT700-24T

#### PRODUCT CODE MT202 6-Bay Smart Charger

The MT202 6-Bay Smart Charger Kit (ACC-001-596) charges the hot-swappable MT202 batteries for the MT700-24T and MT500-24T series Medical Monitors / AIOs. The Kit includes one battery cradle, an AC-DC adapter, and a power cord.


The battery cradle features a DC-input jack, six battery slots, and six LEDs for power and charging indicators. Connect the AC-DC adapter cable to the DC-input jack and then insert the battery packs in the correct directon into each slot for charging.

After inserting the battery pack in the slot, the charging LED lights up (orange) if the battery pack is being recharged. When charging is complete or if the battery pack is already fully charged, the LED will show solid blue.

#### DIMENSIONS

Height = 81.6mm Width = 321mm Depth = 157.6mm

#### PRODUCT ELEVATIONS



72 FREEWAY MED-TECH - ACCESSORIES

#### MT202 - 6-BAY SMART CHARGER

#### TECHNICAL SPECIFICATIONS

| I/O Ports                          |  |
|------------------------------------|--|
| DC-in                              | 1  |
| Charging Slot                      | 6  |
| Mechanical and Environmer          | ntal   |
| AC/DC Adaptors                     | Input: 100 - 240V AC; Output: 19V DC, 10.52A |
| Dimensions $(H \times W \times D)$ | 81.6 x 321 x 157.6 mm                        |
| Weight                             | 1.3kg  |
| Regulatory                         | FCC Class B, CE, C-Tick, RoHS compliant      |
| Temperature                        | Operation: 0°C – 40°C; Storage: -20°C – 60°C |
| Humidity                           | 0% – 90% non-condensing                      |

\*Specifications subject to change without notice.

#### PRECAUTIONS

- 1. Always exercise care when operating and handling.
- 2. Do not disassemble any portion of the charger and adapter as this will void any product warranty.
- 3. Do not use any power adapter other than the one provided with the device or acquired from the manufacturer or its partners.
- 4. In the unlikely event that abnormal noise, strange odour, or smoke is present, immediately disconnect all power sources. Please report the problem to your device provider immediately.



#### Charging status LEDs Clear at-a-glance visual of charging status via individual LEDs.

Blue - fully charged battery Orange - charging battery



| AC-DC           |  |
|-----------------|--|
| power adaptor   |  |
| with power cord |  |







## PRODUCT CLEANING AND USE OF

#### Cleaning the Freeway Med-Tech Medical Grade AIO Monitor PCs for better infection control

**Step I.** Freeway Med-Tech recommend the use of healthcare disposable alcohol based anti-bacterial wipes only on the electrical equipment (approx. 70% alcohol) – such as commonly used Clinell Green Wipes.

**Step 2.** It is recommended wiping from the front of the screen first in a top to bottom motion and then finish across the bottom (the front panel is IP65 Rated). This methodology is designed to minimises the amount of streaking on the screen and reduce excess moisture collecting on the lower front screen bezel, reducing the risk of moisture entering via the lower I/O, remembering to clean the lower OSD keys in the lower right hand corner. After the front Screen has been cleaned, dispose of this wipe.

**Step 3.** With a fresh Wipe, clean the rear of the AIO PC (the rear panel is IPX2 rated). To clean the screen of AIO PC for general house keeping - use either a microfibre cloth with an alcohol based cleaning spray (approx. 70% alcohol) or disposable alcohol based cloth.



All monitor/AIO front panels are IP65 Rated

## INDUSTRY CHEMICALS



#### Suitable Cleaning Chemicals

Given the vast range of cleaning products on the market, it is not possible to list all acceptable brands. We can however, confirm that our products are compatible with cleaning products containing the following chemicals or are from popular cleaning brands. Should you require confirmation of suitable products that are not listed, please contact us with the relevant product data sheet and we will confirm suitability with our in-house specialist.

| Cleaner                            | Brand              |
|------------------------------------|--------------------|
| Viraguard®                         | Veridien           |
| Sani-Cloth® HB                     | PDI                |
| Sani-Cloth® PLUS                   | PDI                |
| Super Sani-Cloth®                  | PDI                |
| CaviWipes™                         | Metrex             |
| Super HDQ®L 10                     | Spartan            |
| Cloro-Wipe Towelette               | Surgipath          |
| Healthcare Hydrogen Peroxide Wipes | Clorox Healthcare® |
| Virex®                             | Johnson            |
| 70% Isopropyl Alcohol              | Multiple suppliers |
| Alcohol Prep Pads                  | PDI, others        |

#### Suitable generic chemicals:

- Alcohol (Ethyl or Isopropyl) Solutions\*
- Alcohol Wipes (Ethyl or Isopropyl)\*
- Hydrogen Peroxide Solutions\*

#### Cleaning procedure for nylon modified polyester coated surfaces:

- Painted surfaces should be cleaned using a soft damp non abrasive cloth and polished dry
- Continual exposure to wet conditions is likely to result in rusting/or the paint lifting.
   **ALWAYS DRY THE SURFACE AFTER CLEANING**
- Continual use of cleaning products may result in a dulling of the surface.
- DO NOT use solvents, bleach, abrasives, synthetic detergents, wax polishes or aerosol sprays unless otherwise listed in the above list.

\*Solutions must ALWAYS be diluted in accordance the with manufacturer's instructions for use on medical products/furniture.

 $f \lambda$  \*The application of the cleaning solution MUST be in accordance the with manufacturer's instructions for use on medical products/furniture.

#### FREEWAY ●●● Med-Tech●●●



#### MEDICAL GRADE AIO PCs & MONITORS PLUS ACCESSORIES

#### Freeway Med-Tech

Unit 14, Colthrop Business Park, Colthrop Lane, Thatcham, Berkshire, RG19 4NB.

Tel: 01635 866 717 Fax: 01635 866 347 Web: freewaymedtech.com Email: sales@freewaymedtech.com

FREEWAYMEDTECH.COM