

## MT400-24TF AIO Mains Powered 24in Medical PC

### TECHNICAL SPECIFICATIONS

System	
CPU	Intel® Core™ i5-14400T 14th Gen, up to 4.5GHz - 10 core Intel® Core™ i7-14700T 14th Gen, up to 5.2GHz - 20 core
RAM	8GB to 64GB
Storage	256Gb to 4TB Flash (mPCIe NVMe type SSD)
Operating System	Microsoft® Windows® 10/I I IoT Enterprise
Display	23.8in capacitive touch screen
Display resolution	1920x1080
Trusted platform module	TPM 2.0
Battery Pack	Optional integrated UPS battery x 1
Buttons	1 power and 4 programmable buttons
Microphone and speaker	Built-in microphones and speaker
Network Interface	
WLAN	Wi-Fi 802.11ax, 2.4GHz/5GHz dual band
Bluetooth	Bluetooth 5.1 LE
I/O Ports	
USB Ports	USB 3.2 x 4 (Type-A) USB 2.0 x 2 (Type-A) USB 2.0 x 1 (Type-C)
COM Port	3
HDMI-out (1.4a)	1 (ESD protection: ±8KV by air, ±4KV by contact)
Audio Jack	1
Ethernet	RJ45 connector x 2 (ESD protection: ±30KV by air, ±30KV by contact)
DC-in	1
Potential Equalization Conductor	1 (optional)
Mechanical/Environmental	
Fan/Fanless	Fanless
AC/DC Adaptor	Input: 100 – 240V AC; Output: 19V DC, 6.31A
Enclosure	Aluminum alloy, antimicrobial enclosure
Dimensions (H x W x D)	370.5 x 567 x 45.2mm
Weight	7.5kg
VESA-compliant mounting	100mm x 100mm VESA standard
Water Resistance	Front panel: IP65; Enclosure: IPX2
Regulatory	ANSI/AAMI ES60601-1, IEC60601-1, IEC60601-1-2, FCC Part 18, FCC Part 15 Class B, GB 17625.1, GB 4943.1, GB/T 9254, CE-EMC, CE-RED, Energy Star 8.0, RCM, CCC
Major options	
Camera	5M front camera
NFC/RFID reader	HF 13.56 MHz, ISO 15693, 14443A(B) & 18000-3 Mode 1, or Dual Frequency (125 kHz & 13.56 MHz)
Smart Card/CAC Reader	Full-slot, reads ISO 7816 T=0, T=1; 1.8/3/5V smart card

\*Specifications subject to change without notice.

### MAIN FEATURES



Mains powered



Optional DC-out



Choice of processor



Windows IoT Enterprise



Water resistant enclosure



Anti-microbial coating



Touch screen

### DIMENSIONS

370.9 x 564.4 x 41.2mm (HxWxD)



### REAR I/O



### RELATED PRODUCTS

MT101



MT102



MT103



MT105

